

# **A computer program for the calculation of three dimensional fluid flow and heat transfer during keyhole mode laser welding**

**R. Rai, H. Zhao, G. G. Roy and T. DebRoy**  
**Department of Materials Science and Engineering**  
**The Pennsylvania State University**

## **INDEX**

1. Model Capabilities	2
2. Special features of the program	2
3. Input file	2
4. Output files	4
5. Calculation Procedure	6
6. Major components of the code	7
a. Calculation of keyhole geometry	7
Assumptions	7
Energy balance on keyhole wall	7
Consideration for plasma absorption and multiple reflections	9
b. Three dimensional fluid flow and heat transfer	11
Governing equations	11
Boundary conditions	12
Turbulence model	13
Solution methodology	14
Convergence criterion	15
7. Remarks about the code	
a. User modifiable sections of the code	15
b. Header.for	15
8. Case studies	
<u>Case 1</u> : Tantalum welds made with 1900 W input power and 12.7 mm/s welding speed.	16
<u>Case 2</u> : Vanadium welds made with 1980 W input power at 25.4 mm/s welding speed.	23
<u>Case 3</u> : 304L stainless steel welds made with 1980 W input power at 19.1 mm/s welding speed.	30
<u>Case 4</u> : Ti-6Al-4V welds made with 1400 W input power at 16.9 mm/s welding speed.	37
9. Plotting of results	44
10. Concluding remarks	44
11. References	45























































































